

**SECTION 1: Identification**

**1.1. Identification**

Product name : DIESEL LIFELINE  
Product code : 103092 and 103093

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : Diesel Fuel Additive

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

R.B. Howes & Co., Inc.  
3511 North Ohio Street  
Wichita, KS 67219 - USA  
T 401-294-5500, 1-800 GET HOWES (438-4693)

**Manufacturer**

R.B. Howes & Co., Inc.  
35 Regan Road  
Brampton, ON L7A 1B2 - Canada  
T 401-294-5500, 1-800 GET HOWES (438-4693)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC 1 (800) 424-9300 / 703-527-3887

**SECTION 2: Hazard identification**

**2.1. Classification of the substance or mixture**

**GHS classification**

Flam. Liq. 4  
Skin Irrit. 2  
Carc. 2  
Asp. Tox. 1

**2.2. Label elements**

**GHS labelling**

Hazard pictograms (GHS) :



GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Combustible liquid.  
Causes skin irritation.  
Suspected of causing cancer.  
May be fatal if swallowed and enters airways.

Precautionary statements (GHS) :

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, open flames, sparks. No smoking.  
Wash hands thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If exposed or concerned: Get medical advice/attention.  
If swallowed: Immediately call a poison center/doctor.  
Do NOT induce vomiting.  
If on skin: Wash with plenty of water.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice/attention.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity**

Not applicable

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
Organic Solvent	Trade Secret	15 - 40
Petroleum Distillates 1	Trade Secret	10 - 30
Petroleum Distillates 2	Trade Secret	10 - 30
Petroleum Distillates 3	Trade Secret	10 - 30
Aromatic Hydrocarbon	Trade Secret	1 - 5

\*The exact chemical identity and/or exact percentages (concentration) of each ingredient has been held as confidential business information (CBI). Refer to Section 15 for additional information regarding this CBI claim.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon.
- Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water spray.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Eliminate sources of ignition. Use only non-sparking tools. Spilled material may present a slipping hazard.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Handle in well-ventilated areas.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Organic Solvent		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
IDLH	US IDLH (ppm)	600 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
NIOSH	US-NIOSH chemical category	Potential for dermal absorption
Petroleum Distillates 1		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total hydrocarbon vapor)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Petroleum Distillates 2		
Not applicable		
Petroleum Distillates 3		
Not applicable		
Aromatic Hydrocarbon		
ACGIH	ACGIH TWA (ppm)	10 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	10 ppm

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Aromatic Hydrocarbon		
IDLH	US IDLH (ppm)	250 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	15 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Clear
Odour	: Distinctive
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 179.4 °C IBP (354.92°F), FBP 294°C (561.2°F) ASTM D86
Flash point	: ≥ 66 °C (151 °F) [Closed cup]
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 26.88 @ 60°F ASTM D4052
Solubility	: Water: insoluble in water
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 1.805 cSt @ 40°C (104°F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

May form flammable/explosive vapour-air mixture. Stable under normal conditions.

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Sources of ignition. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May release flammable gases. May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

Organic Solvent	
LD50 oral rat	5.35 g/kg
LD50 dermal rabbit	9500 mg/kg

Petroleum Distillates 1	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

Petroleum Distillates 2	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2180 mg/m <sup>3</sup> (Exposure time: 4 h)

Petroleum Distillates 3	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat	> 590 mg/m <sup>3</sup> (Exposure time: 4 h)

Aromatic Hydrocarbon	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat	> 340 mg/m <sup>3</sup> (Exposure time: 1 h)

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Not classified.  
Respiratory or skin sensitisation : Not classified.  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Suspected of causing cancer.

Aromatic Hydrocarbon	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified.  
STOT-single exposure : Not classified.  
STOT-repeated exposure : Not classified.  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.  
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Organic Solvent	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum Distillates 2	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum Distillates 3	
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Aromatic Hydrocarbon	
LC50 fish 1	5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

#### 12.2. Persistence and degradability

DIESEL LIFELINE	
Persistence and degradability	Not established.

#### 12.3. Bioaccumulative potential

DIESEL LIFELINE	
Bioaccumulative potential	Not established.
Organic Solvent	
Partition coefficient n-octanol/water	-0.064 (at 20 °C)
Petroleum Distillates 3	
BCF fish 1	61 - 159
Partition coefficient n-octanol/water	2.9 - 6.1
Aromatic Hydrocarbon	
BCF fish 1	30 - 430
Partition coefficient n-octanol/water	3.6

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Aromatic Hydrocarbon	
1990 Hazardous Air Pollutant (Clean Air Act)	Yes

Other information : No other effects known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapours are flammable.

# DIESEL LIFELINE

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 14: Transport information

#### Department of Transportation (DOT) / Transportation of Dangerous Goods (TDG)

In accordance with DOT / TDG

UN-No.(DOT / TDG)	: UN1268
Proper Shipping Name (DOT / TDG)	: Petroleum distillates, n.o.s.
Class (DOT / TDG)	: Combustible liquid
Packing group (DOT / TDG)	: III

#### Transport by sea

This product is currently not packaged to comply with IMDG regulations. It is not intended to be shipped by sea.

#### Transport by air

This product is currently not packaged to comply with IATA regulations. It is not intended to be shipped by air.

### SECTION 15: Regulatory information

#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Aromatic Hydrocarbon	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
CERCLA RQ	100 lb


All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Canada WHMIS Confidential Business Information (CBI): HMIRA registry number **XXXXXXXX**. The date of filing is **YYYY-MM-DD**.

#### 15.2. International regulations

No additional information available

#### 15.3. US State regulations


 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

Date of issue	: 04/16/2018
Revision date	: 01/20/2020
Other information	: None.
Prepared by	: Nexreg Compliance Inc. <a href="http://www.Nexreg.com">www.Nexreg.com</a>



NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



#### Indication of changes:

HMIRA registry number. HMIRA submission date. Physical and chemical properties.

SDS HazCom 2012 - WHMIS 2015 (NexReg) - Section 15

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*